Model: RS-M6UFO

17 CM MID-RANGE SPEAKER
1.5" CCAW Voice Coil

SPECIFICATIONS

General Data		Unit
Overall Dimensions	173 x 78	mm
Nominal Power Handing	150	W
Maximum Power	300	W
Sensitivity	95	dB
Frequency Response	120~15000	Hz
Cone Material	Pulp Paper	
Basket	Steel	
Net Weight	2.2	kg
Electrical Data		
Nominal Impedance	4	Ohm
DC Resistance	3.2	Ohm
Voice Coil and Magnet Parameters		
Voice Coil Diameter	38.6	mm
Voice Coil Height	8	mm
Magnetic Gap Height	6	mm
Voice Coil Robbin	Kapton	
Number of Layers	2L	
T-S Parameters		
Suspension Compliance	139.634μM/N	Cms
Mechanical Q Factor	5.63	Qms
Electrical Q Factor	0.564	Qes
Total Q Factor	0.513	Qts
Moving Mass	10.224g	Mms
Eq. Cas AIR Loaded	4.694L	Vas
Resonant Frequency	133.201Hz	Fs
Effective Piston Area	153.860cm^2	SD

FEATURES

- Steel Basket
- Reinforced Pulp Paper Cone, Treated Cloth Surround
- Dome Paper Dust Cap
- High Temperature 1.5Inch CCAW Voice Coil
- Ferrite Magnet Structure

Dimensions



