Model:SX-M52XS

5.25" MIDRANGE SPEAKER

SPECIFICATIONS

General Data		Unit
Overall Dimensions	134*56.8	mm
Nominal Power Handing	50	W
Maximum Power	100	W
Sensitivity	91	dB
Frequency Response	130-15K	Hz
Cone Material	PAPER CONE	
Basket	METAL	
Net Weight	0.37	kg
Electrical Data		
Nominal Impedance	4	Ohm
DC Resistance	3.2	Ohm
Voice Coil and Magnet Parameters		
Voice Coil Diameter	Φ25.5	mm
Voice coil wire	CCAW	
Voice Coil Height	6	mm
Magnetic Gap Height	4	mm
Magnet system type	High Flux Ferrite	
Voice Coil Bobbin	KAPTON	
Number of Layers	2L	
T-S Parameters		
Suspension Compliance	0.2979	Cms
Mechanical Q Factor	5.09	Qms
Electrical Q Factor	2.18	Qes
Total Q Factor	1.53	Qts
Moving Mass	5.2355	Mms
Eq.Cas AIR Loaded	3.1189	Vas
Resonant Frequency	135	Fs
Effective Piston Area	8.66E+01	SD

Features

13 CM MIDRANGE SPEAKER

BLACK PAPER CONE WITH CLOTH EDGE

IMPEDANCE:4Ω

RATED POWER:50W

MAX.POWER:100W

FREQUENCY RESPONSE:130-15KHZ

SENSITIVITY:91DB

Dimensions



