Model:SX-M69VK

6X9" MIDRANGE SPEAKER

SPECIFICATIONS

General Data		Unit
Overall Dimensions	236*178*102.5	mm
Nominal Power Handing	200	W
Maximum Power	400	W
Sensitivity	92	dB
Frequency Response	100-15K	Hz
Cone Material	PAPER CONE	
Basket	METAL	
Net Weight	1.87	kg
Electrical Data		
Nominal Impedance	4	Ohm
DC Resistance	3.2	Ohm
Voice Coil and Magnet Parameters		
Voice Coil Diameter	Φ38.6	mm
Voice coil wire	CCAW	
Voice Coil Height	8.5	mm
Magnetic Gap Height	6	mm
Magnet system type	High Flux Ferrite	
Voice Coil Bobbin	KAPTON	
Number of Layers	2	
T-S Parameters		
Suspension Compliance	0.2161	Cms
Mechanical Q Factor	5.66	Qms
Electrical Q Factor	0.75	Qes
Total Q Factor	0.67	Qts
Moving Mass	14.2104	Mms
Eq.Cas AIR Loaded	15.1843	Vas
Resonant Frequency	90.82	Fs
Effective Piston Area	2.24E+02	SD

Features

6X9" MIDRANGE SPEAKER

BLACK PAPER CONE WITH CLOTH EDGE

IMPEDANCE:4Ω

RATED POWER:200W

MAX.POWER:400W

FREQUENCY RESPONSE:100-15KHZ

SENSITIVITY:92DB

Dimensions



