Model:SX-MX6

6.5" MIDRANGE SPEAKER

SPECIFICATIONS

General Data		Unit
Overall Dimensions	166*67	mm
Nominal Power Handing	140	W
Maximum Power	250	W
Sensitivity	92	dB
Frequency Response	100-15K	Hz
Cone Material	PAPER CONE	
Basket	METAL	
Net Weight	1.25	kg
Electrical Data		
Nominal Impedance	4	Ohm
DC Resistance	3.2	Ohm
Voice Coil and Magnet Parameters		
Voice Coil Diameter	Φ25.5	mm
Voice coil wire	CCAW	
Voice Coil Height	5	mm
Magnetic Gap Height	6	mm
Magnet system type	High Flux Ferrite	
Voice Coil Bobbin	KAPTON	
Number of Layers	2L	
T-S Parameters		
Suspension Compliance	0.1371	Cms
Mechanical Q Factor	7.4912	Qms
Electrical Q Factor	2.0653	Qes
Total Q Factor	1.619	Qts
Moving Mass	6.3199	Mms
Eq.Cas AIR Loaded	3.9213L	Vas
Resonant Frequency	160	Fs
Effective Piston Area	0.0143	SD

Features

16 CM MIDRANGE SPEAKER

BLACK PAPER CONE WITH CLOTH EDGE

IMPEDANCE:4Ω

RATED POWER:140W

MAX.POWER:250W

FREQUENCY RESPONSE:100-15KHZ

SENSITIVITY:92DB

Dimensions



