Model:SX-M82GX

8" MIDRANGE SPEAKER

SPECIFICATIONS

General Data		Unit
Overall Dimensions	202*80.5	mm
Nominal Power Handing	125	W
Maximum Power	250	W
Sensitivity	92	dB
Frequency Response	90-15K	kg
Cone Material	PAPER CONE	
Basket	METAL	
Net Weight	0,98	kg
Electrical Data		
Nominal Impedance	4	Ohm
DC Resistance	3,2	Ohm
Voice Coil and Magnet Parameters		
Voice Coil Diameter	Φ25.5	mm
Voice coil wire	KCCAW	
Voice Coil Height	6	mm
Magnetic Gap Height	4	mm
Magnet system type	High Flux Ferrite	
Voice Coil Bobbin	KAPTON	
Number of Layers	2L	
T-S Parameters		
Suspension Compliance	0,2330	Cms
Mechanical Q Factor	10,86	Qms
Electrical Q Factor	1,76	Qes
Total Q Factor	1,52	Qts
Moving Mass	11,9938	Mms
Eq.Cas AIR Loaded	16,7591	Vas
Resonant Frequency	98	Fs
Effective Piston Area	2,27E+02	SD

Features

20 CM MIDRANGE SPEAKER

BLACK PAPER CONE WITH CLOTH EDGE

IMPEDANCE:4Ω

RATED POWER:125W

MAX.POWER:250W

FREQUENCY RESPONSE:90-15KHZ

SENSITIVITY:92DB

Dimensions



