Model:SX-M65GX

6.5" MIDRANGE SPEAKER

SPECIFICATIONS

General Data		Unit
Overall Dimensions	165.6*70	mm
Nominal Power Handing	90	W
Maximum Power	180	W
Sensitivity	92	dB
Frequency Response	100-15K	Hz
Cone Material	PAPER CONE	
Basket	METAL	
Net Weight	0,75	kg
Electrical Data		
Nominal Impedance	4	Ohm
DC Resistance	3,2	Ohm
Voice Coil and Magnet Parameters		
Voice Coil Diameter	Φ25.5	mm
Voice coil wire	KCCAW	
Voice Coil Height	6	mm
Magnetic Gap Height	4	mm
Magnet system type	High Flux Ferrite	
Voice Coil Bobbin	KAPTON	
Number of Layers	2L	
T-S Parameters		
Suspension Compliance	0,3214	Cms
Mechanical Q Factor	5,41	Qms
Electrical Q Factor	1,36	Qes
Total Q Factor	1,08	Qts
Moving Mass	6,9885	Mms
Eq.Cas AIR Loaded	8,6613	Vas
Resonant Frequency	96	Fs
Effective Piston Area	1,39E+02	SD

Features

16 CM MIDRANGE SPEAKER

BLACK PAPER CONE WITH CLOTH EDGE

IMPEDANCE:4Ω

RATED POWER:90W

MAX.POWER:180W

FREQUENCY RESPONSE:100-15KHZ

SENSITIVITY:92DB

Dimensions



