

Model: RS-VP5

13 CM 2Way Component Speaker



SPECIFICATIONS

General Data		Unit
Overall Dimensions	Ø129 x 63	mm
Nominal Power Handling	70	W
Maximum Power	140	W
Sensitivity	88	dB
Frequency Response	100~10000	Hz
Cone Material	PP	
Basket	Steel	
Net Weight	0.85	kg

FEATURES
Steel Basket
Plated Injection PP Cone With Surround
Dome Paper Dust Cap
High Temperature Voice Coil, Ferrite Magnet Structure
Include 1" Voice Coil Dome Tweeter & Crossover

Electrical Data		
Nominal Impedance	4	Ohm
DC Resistance	3.2	Ohm

Voice Coil and Magnet Parameters		
Voice Coil Diameter	25.9	mm
Voice Coil Height	11	mm
Magnetic Gap Height	5	mm
Voice Coil Robbin	Kapton	
Number of Layers	2L	

T-S Parameters		
Suspension Compliance	183.698µM/N	Cms
Mechanical Q Factor	4.814	Qms
Electrical Q Factor	0.892	Qes
Total Q Factor	0.753	Qts
Moving Mass	8.302g	Mms
Eq. Cas AIR Loaded	2.687L	Vas
Resonant Frequency	103.707Hz	Fs
Effective Piston Area	81.67cm ²	SD

Dimensions

